



We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by: **PROLINK**

Discription

ProLink F/O PIGTAIL, SC/PC-MM-1M OM4

Features

-  Low insertion loss, high return loss.
-  Excellent mechanical endurance.
-  High credibility and stability.
-  Good in repeatability and exchangeability.
-  Insert-pull, key-oriented coupling mechanism which allows high repeatable, low-loss connection Simplex, Duplex, and Multi-core accessories for standard or customized structure.
-  PC/UPC/APC Polish.
-  Comply with TelcordiaGR-326-CORE Speciation.
-  The material of the plastic plug complies with the request of UL94V-O and the Standard of RoHS



Description

Items	Specifications 50/125
Type	OM4 50/125 Fiber
Application	Communication
Cortication	RoHS, UL, CE, ISO9001
Allowed Lateral Pressure	100 (N/100mm)<1000 (N/100mm)
Allowed Tensile Strength	Allowed Tensile Strength
Core	Core
Sheath Material	PVC - LSZH
Connection Structure	PC-LC
Export Markets	Export Markets

Items	Unit	Speciation
Insertion loss	dB	≤0.25
Max. Insertion loss	dB	≤0.30
Repeatability	dB	≤0.10
Changeability	dB	≤0.20
Return loss	dB	≥28
Operation Temperature	°C	-20~+60
Storage temperature	°C	-20~+50
Fiber type	um	50/125
Core number		Single
Durability		>1000times