



We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by: 

Description

Prolink Media Converter 10/100/1000M base-TX/FX MM, 2k

Features

-  **10/100/1000Mbps Copper Port**
-  **1000Mbps Fiber Port**
-  **Full wire speed conversion**
-  **Auto MDI/MDI-X**
-  **Supports jumbo packets up to 2K bytes**
-  **High-Efficiency SRAM for packet buffer**
-  **Options for Bi-Directional communication**
-  **Options for CWDM communication**
-  **Optional DIN Rail mounting**
-  **Stand-alone or chassis installation in MCC-14R chassis**



Specifications

Standards	IEEE 802.3, 802.3ab, 802.3u, 802.3z
Copper Port (TP)	Shielded RJ-45 jack Cat5 UTP cable up to 100m Auto-negotiation for speed and duplex Forced mode with speed and duplex settings Speed for 10Mbps or 100Mbps, Full-duplex or Half-duplex support
Fiber Port (FX)	Forced 100Mbps, Full-duplex (factory default) Far end fault detection Multi-Mode: 50/125 and Single Mode: 9/125
LEDs	Power Status Link/Activity Speed Duplex
Power Input	+5VDC
Environment	Operating Temperature: -5° C ~ 55° C Storage Temperature: -20° C ~ 70° C Humidity: 5% ~ 90% non-condensing
Dimensions	3.70 x 2.79 x 1.02 inches (94 x 71 x 26 mm)