



We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Description

Prolink Media Converter 10/100/1000M base-TX/FX SM, 20k

Features

-  10/100/1000Mbps Copper Port
-  1000Mbps Fiber Port
-  Full wire speed conversion
-  Auto MDI/MDI-X
-  Supports jumbo packets up to 20K bytes
-  High-Efficiency SRAM for packet buffer
-  Options for Bi-Directional communication
-  Options for CWDM communication
-  Optional DIN Rail mounting
-  Stand-alone or chassis installation in MCC-14R chassis



Specifications

Standards	IEEE 802.3, 802.3ab, 802.3u, 802.3z
Copper Port (TP)	Shielded RJ-45 jack Cat5 UTP cable up to 100m Auto-negotiation for speed and duplex Forced mode with speed and duplex settings Speed for 10Mbps or 100Mbps, Full-duplex or Half-duplex support
Fiber Port (FX)	Forced 100Mbps, Full-duplex (factory default) Far end fault detection Multi-Mode: 50/125 and Single Mode: 9/125
LEDs	Power Status Link/Activity Speed Duplex
Power Input	+5VDC
Environment	Operating Temperature: -5° C ~ 55° C Storage Temperature: -20° C ~ 70° C Humidity: 5% ~ 90% non-condensing
Dimensions	3.70 x 2.79 x 1.02 inches (94 x 71 x 26 mm)