



We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Description

Prolink Media Converter 10/100M base-TX/FX MM, 20k

Features

-  10/100Mbps Copper to 100Mbps Fiber
-  Full wire speed conversion
-  Auto-negotiation, auto MDI/MDI-X detection
-  Link fault pass through function
-  Far End Fault function
-  Stand-alone or chassis installation in MCC-14R
-  Optional DIN rail mounting
-  Low power consumption
-  Wide range of fiber options



Specifications

Standards	IEEE 802.3, 802.3u
Copper Port (TP)	Shielded RJ-45 jack Cat5 UTP cable up to 100m Auto-negotiation for speed and duplex Forced mode with speed and duplex settings Speed for 10Mbps or 100Mbps, Full-duplex or Half-duplex support
Fiber Port (FX)	Forced 100Mbps, Full-duplex (factory default) Far end fault detection Multi-Mode: 50/125 and Single Mode: 9/125
LEDs	Power Status Link/Activity Speed Duplex
Power Input	+5VDC
Environment	Operating Temperature: -5° C ~ 55° C Storage Temperature: -20° C ~ 70° C Humidity: 5% ~ 90% non-condensing
Dimensions	3.70 x 2.79 x 1.02 inches (94 x 71 x 26 mm)